

# Technical Specifications

Model S6080HK	DT140A
<b>Processor &amp; Speed</b>	AMD Athlon(T) XP2400+ 2.0 GHz/266
<b>Chipset</b>	nForce2-IGP
<b>Motherboard</b>	Explorer2-GL6E (A7NBX-LA)
<b>RAM</b>	256/2700 MB 333 DDR SDRAM
Maximum	2 GB (2x1024MB DDR SDRAM)
Sockets	Two 184-pin DDR DIMMs
Size	128, 256, 512 and 1024 MB DDR DIMMs
<b>Free DIMM Sockets</b>	One
Pairs Required	No
Type Supported	JEDEC unbuffered DDR SDRAM DIMM specification
<b>Cache</b>	128 KB L1, 256 KB L2 Integrated on Processor module
<b>Hard Drive</b>	40 GB (5400 RPM)
<b>Optical Drive</b>	CD-RW Drive: 48x-Write / 24X-Re-write/CD-ROM speed =48x max.
Average Random Access	110ms
Transfer Rate	6.0MB/sec.
<b>Diskette Drive</b>	3.5" (1.44MB)
<b>Video Graphics</b>	AGP 8X, Integrated
Controller	nVidia nForce2
Video Memory	64MB UMA, not upgradeable
<b>Network Card</b>	10/100 BaseT, Integrated
<b>1394 Card</b>	IEEE-1394, Integrated
<b>Sound</b>	AC'97, 6 Channel, Integrated on MB
Controller	Realtek ALC650F
<b>Chassis</b>	Chameleon, 250HV
<b>USB Interface Specification</b>	USB 2.0
<b>External Ports</b>	6= USB, 1= serial, 1= parallel; 2= 1394
Front I/O Connector	2= USB, 1=1394, 1=Microphone; 1= Headphone
<b>Expansion Slots (Total)</b>	3= PCI, 1= AGP
<b>Expansion Slots (FREE)</b>	2= PCI, 1= AGP
<b>Drive Bays (Total)</b>	Two 5.25" external, One 3.5" external, Two 3.5" internal
<b>Drive Bays (FREE)</b>	One 5.25" external, One 3.5" internal
<b>Keyboard/Mouse</b>	One-touch Enhanced Keyboard, PS/2 Optical scrolling mouse

---

Copyright Hewlett-Packard Co. 1994-2003  
This information is subject to change without notice and  
is provided "as is" with no warranty.  
Hewlett-Packard shall not be liable for any direct,  
indirect, special, incidental or consequential damages  
in connection with the use of this material.